

INSTRUCTIONS: Moz Tides Wall Systems “Quick-Spec” Guideline

Note: This specification guideline is provided in Microsoft Word format (.doc). It includes several imbedded notes (highlighted in blue text) to assist the specifying architect. Any text may be deleted or edited as necessary. To adapt specification to your specific project:

- Save this document to disk “as is” with all notations and instructions, for future use.
- Open this document. Begin review of contents.
- Select (and retain) desired material style information. (Delete information pertaining to finish not selected and delete blue-highlighted text.)
- Select (and retain) desired finish specification information. (Delete information pertaining to finish not selected and delete blue-highlighted text)
- Make sure all blue instructional copy is deleted and adjust vertical spacing, if needed.
- Choose “Save as” under the “File” tab (at top listing) and indicate a project-specific name. This will save modified specification to your computer for use as needed with project specification documents.

Feel free to call our sales department should you have any questions regarding the specification of our products. Moz Designs (510) 632-0853 x 24 for Moz Custom Sales

DIVISION 5: MOZ METAL TIDES WALL SYSTEMS

PART 1 – GENERAL

1.01 SUMMARY

- A. Extent of Tides System as shown on drawings and schedules
- B. Drawings and general provisions of the Contract Documents apply to work of this section.

1.02 SUBMITTALS

Note to Specifier: Revise Section number in paragraph below as appropriate

- A. Submit the following in accordance.
 1. Product Data: Manufacturer's product literature for the column specified.
 2. Shop Drawings: Indicate thickness and dimension of parts, Snap bars and anchoring methods, and detail and location of joints.
 3. Samples
 - a. Two samples of each finish in color or colors selected, 5” x 7”
 4. Affidavit certifying that the material meets the requirements specified.

1.03 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials to the project site in manufacturer's original crating, properly labeled for identification and installation purposes. Materials to be stored in fully enclosed space where they will be protected against damage from moisture, direct sunlight, surface contamination and other causes.

PART 2 – PRODUCTS

2.01 MANUFACTURER

- A. Subject to compliance with requirements, provide products from the following manufacturer:

MóZ Designs, Inc. 711 Kevin Court, Oakland, CA 94621

Phone 510-632-0853 • Fax 510-632-0852

Contact: Linda Barfield, Ext 24 linda@mozdesigns.com

- B. Moz Designs Series <Type in your Moz Tides type i.e. Breaking, Ocean or Rolling Waves here>

2.02 MATERIALS AND FABRICATION

- A. Standard Tides System: Formed .065” Aluminum or 18 gauge stainless. *Refer to the Website for standard sizes or contact manufacturer for details*
- B. Tides System will consist of standard panel sizes, true to shape, accurate in size, square, and free from distribution or manufacturing defects.
- C. All seams shall have Butt joints as shown on drawings.
- D. System will have “mid” and “end” Snap Bar clips as shown on drawings.

2.03 ACCESSORIES

- A. Fasteners shall be concealed, as recommended by the manufacturer.

2.04 FINISHES

- A. Moz Metal finishes are applied to pre-formed material by factory. Post forming is not recommended. Contact manufacturer for details.
1. Color: *Choose a Color from manufacturer’s standard colors. Custom colors are available but are subject to an additional cost; contact manufacturer for details*
 2. Pattern: *Choose a Pattern from manufacturer’s standard pattern selection.*
 3. Provide factory applied removable plastic film for protection during fabrication and installation.

PART 3 – EXECUTION

3.01 EXAMINATION

- A. Examine the areas and conditions under which materials are to be installed and notify the [Contractor] [Construction Manager] in writing of conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions have been corrected.
- B. Surfaces to receive Tides Wall Systems shall be even, smooth, sound, clean, dry and free from defects.

3.03 INSTALLATION

- A. Install Tides Wall Systems in accordance with manufacture’s written instructions and shop drawings.
- B. All support blocking structures to be supplied by general contractor.
- C. Tides Wall Systems shall be erected plumb, level, square, true to line, secured and in proper alignment and relationship to other work of other trades.
- D. Tides Wall Systems shall be inspected before installation to be free of dents, scratches and other defects prior to installation.

3.04 ADJUSTING AND CLEANING

- A. Removal of Protective covering shall occur immediately after installation to prevent adhesive transfer
- B. Clean exposed Tides Wall Systems surfaces promptly after installation in accordance with recommendations of Tides Wall Systems and coating manufacturers.
- E. Protection of Tides Wall Systems from damage by other trades after installation to be provided General Contractor.

END OF SECTION